## **Final Exam**

## **Graduate Accelerator Physics**

Final Exam

## Dec. 12, 2017

- 1. (15 pts) The JLEIC's detector solenoid has a length of 6 m and a magnetic field of 1 T. What is the focal length of the solenoid for 100 GeV protons in m, assuming the lens is thin. Is the lens thin? (Extra Credit: 5 pts) What is the matched  $\beta$  (the value of the  $\beta$  leading to constant size throughout the solenoid)?
- 2. (20 pts) In our coupled pendulum model  $\omega_{g}$  is  $20\pi \sec^{-1}$  and  $\omega_{s}$  is  $0.5\pi \sec^{-1}$ .
  - a. What are the mode frequencies  $\omega_{\perp}$  and  $\omega_{-}$ ?
  - b. The first ball is struck in the direction of the spring. How long does it take the resulting oscillation energy to transfer completely to the second ball?
- 3. (25 pts) You are a young Geoff Krafft and just showed up at Jefferson Lab in 1986. The CEBAF/Cornell cavity had just been chosen for the CEBAF project. It has the following parameters: R/Q=480  $\Omega$ , f=1.5 GHz,  $Q_0$ =2.4×10<sup>9</sup>, Energy Gain=2.5 MV. The maximum project operating current has been specified as 800  $\mu$ A. The cavity will be operated on crest without detuning and neglect microphonics.
  - a. Show the optimal coupling factor, i.e., that which yields no reflected power at the maximum operating current, is  $\beta_{opt} = 369.64$ .
  - b. What is the consequent loaded  $Q(Q_L)$ ?
  - c. With this coupling, what is the power required at zero current (no beam load)?
  - d. With this coupling, what is the power required at 800  $\mu$ A?
  - e. Compare with the beam power of 800  $\mu$ A×2.5 MV = 2 kW. Does you result make sense?
  - f. (Extra Credit: 5 pts) Suppose the same cavity is used in a storage ring with  $\psi_b = 72^{\circ}$ . What detuning  $\psi$  would lead to minimum incident power?
- 4. (20 pts) Suppose a beam with a single particle distribution function

$$\rho(x,x') = \frac{1}{2\pi\varepsilon} \exp\left[-\left(\gamma x^2 + 2\alpha x x' + \beta x'^2\right)/2\varepsilon\right]$$

with  $\gamma\beta - \alpha^2 = 1$ , comes into a solid target with  $\alpha = 0$  at z = 0.

- a. What is the *rms* size in angle  $\sigma_{x'}$  at z = 0 in terms of  $\beta$  and  $\varepsilon$ ?
- b. Multiple scattering in the target causes the particle angles to be updated as

$$x'_{after} = x'_{before} + \Delta x'$$

where  $\Delta x'$  is distributed according to the distribution function

$$\frac{1}{\sqrt{2\pi}\sigma_r'}\exp\left(-\Delta x'^2/2\sigma_r'^2\right).$$

Calculate the *rms* emittance and *rms* size in angle after the target in terms of  $\beta$ ,  $\varepsilon$ , and  $\sigma'_r$ . You may neglect any update in the position as insignificant. Hint: When you are done the answer will be "the obvious" one. How do spreads in Gaussian distributions add? Of course, I'm asking that you show, by doing the correct statistical calculation, that the obvious answer is correct!

- 5. (20 pts) A soft X-ray source is designed to operate at 4 GeV. A 100 mA electron beam current passes through an undulator with K = 1, N = 100, and  $\lambda_{D} = 2.3$  cm.
  - a. What are the wavelength, frequency, and energy of the photons emitted in the forward direction?
  - b. Given the expressions in the lectures for the total number and the average energy of photons emitted by a single electron, what is the total radiation power emitted by the electrons passing through the undulator?

You may find these integrals useful

$$\frac{1}{\sqrt{2\pi\sigma}} \int_{-\infty}^{\infty} \exp\left[-\frac{x^2}{2\sigma^2}\right] dx = 1$$
$$\frac{1}{2\pi\varepsilon} \int_{-\infty}^{\infty} \exp\left[-\left(\frac{\gamma x^2 + 2\alpha x x' + \beta x'^2}{2\varepsilon}\right)/2\varepsilon\right] dx dx' = 1 \quad \text{when } \gamma\beta - \alpha^2 = 1$$